

AO Size Document Scanner (36 inch) Colortrac L36e



Key features:

- Scan direct to USB stick or to a network via a PC using the Ethernet connection
- User-friendly interface with quick and easy navigation
- Compact 36" design with lightweight scanner takes up minimal space and enables easy set up
- SingleSensor with multiple LED illumination for excellent line definition and accuracy
- Up to 3.0 inches per second scanning; 600 dpi optical resolution
- Scan to TIFF, PDF and JPEG up to 2.27 m in length
- Media thickness up to 0.5mm

Scanext Solution Sdn. Bhd. (Co No. 1150182-P)

No.29-1, Jalan PJU 1A/5A, Ara Damansara,
47301 Petaling Jaya. Selangor. Malaysia.

Tel: +603-7847 2415

Website: <http://www.scanext.com.my>

Email: info@scanext.com.my

SPECIFICATION

Technology	SingleSensor with multiple LED illumination
Scan speed	
300 / 600 dpi Standard	1inch/sec colour, 3 inches/sec mono
Scan Modes	
Scan to USB Thumb Drive	TIFF (No ScanApp Le), JPG, PDF, M-PDF (ScanAppLe available)
Scan to Network PC	TIFF, JPEG, PDF, TiffG4, M-PDF
Scan Accuracy	0.2% +/-1 pixel
Resolution	Maximum: 600 dpi, Optical: 600 dpi
Maximum Image Width	36" / 914.4 mm
Maximum Media Width	38" / 965.2 mm
Maximum scan length	109" / 2768 mm
Maximum & Minimum Media Thickness	Min = 0.07 mm, Max = 0.5 mm
Control Panel User Interface	3" touchscreen (touch pen included)
Scanner Interface	Ethernet 10 / 100 / 1000 Base-T / TX
Scan to USB	USB2, 128GB FAT32
Scan to Network PC	L Scan App, Sets scan directory and file type
OS compatibility :	Windows 7 / 8. x (32 / 64bit)
Included Software	L Scan App software
Physical Dimensions	1238 (W) mm x 146 (D) mm x 131 (H) mm
Weight	6.56 kg
Operating Environments	Temperature: 10-35 °C Humidity: 10-90 %
Scanner Power Consumption	Standby (sleep): 0.05W Idle: 10.20W Scanning: 19.40W
Image Enhancement	Brightness, B&W Threshold, White Point/Black Point Adjustment
Controller	Built In
What's In The Box?	L36e scanner
	CD for L Scan App software
	Calibration Sheet
	power cord
	Ethernet cable
	Touch Pen